

The Set of Diagnostics for the First Operation Campaign of the Wendelstein 7-X Stellarator

Ralf König^{*},¹

E-mail: Ralf.Koenig@ipp.mpg.de

J. Baldzuhn¹, W. Biel², C. Biedermann¹, H. S. Bosch¹, S. Bozhenkov¹, T. Bräuer¹,
B. Brotas de Carvalho³, R. Burhenn¹, B. Buttenschön¹, G. Cseh⁴, A. Czarnecka⁵,
M. Endler¹, V. Erckmann¹, T. Estrada⁶, J. Geiger¹, O. Grulke¹, D. Hartmann¹, D.
Hathiramani¹, M. Hirsch¹, S. Jabłonski⁵, M. Jakubowski¹, J. Kaczmarczyk⁵, T.
Klinger¹, S. Klose¹, G. Kocsis⁴, P. Kornejew¹, A. Krämer-Flecken², T. Kremeyer⁷, M.
Krychowiak¹, M. Kubkowska⁵, A. Langenberg¹, H. P. Laqua¹, M. Laux¹, Y. Liang²,
A. Lorenz¹, A., O. Marchuk², V. Moncada⁸, O. Neubauer², U. Neuner¹, J. W.
Oosterbeek⁹, M. Otte¹, N. Pablant¹⁰, E. Pasch¹, T. S. Pedersen¹, K. Rahbarnia¹, L.
Ryc⁵, O. Schmitz⁷, W. Schneider¹, H. Schuhmacher¹¹, B. Schweer², T. Stange¹, H.
Thomsen¹, J.-M. Travers⁸, T. Szepesi⁴, U. Wenzel¹, A. Werner¹, B. Wiegel¹¹, T.
Windisch¹, R. Wolf¹, G. A. Wurden¹², D. Zhang¹, A. Zimbal¹¹, S. Zoleznik⁴ and the
W7-X Team

¹Max Planck Inst. for Plasma Physics, 17491 Greifswald, Germany

²Institute of Energy- and Climate Research, Forschungszentrum Jülich GmbH, D-52425 Jülich, Germany

³Instituto de Plasmas e Fusão Nuclear Instituto Superior Técnico, Lisbon, Portugal

⁴Wigner RCP, RMI, Konkoly Thege 29-33, H-1121 Budapest, Hungary

⁵IFPiLM, Hery Street 23, 01-497 Warsaw, Poland

⁶Laboratorio Nacional de Física Fundamental, CIEMAT, Avenida Complutense, Madrid, Spain

⁷Univ. of Wisconsin, Dept. of Engineering Physics, 1500 Engineering Drive, Madison, WI 53706

⁸CEA, IRFM, F-13108 Saint-Paul-lez-Durance, France

⁹Eindhoven University of Technology, P.O. Box 513, 5600 MB Eindhoven, The Netherlands

¹⁰Princeton Plasma Physics Laboratory, Princeton, New Jersey 08543, USA

¹¹Physikalisch-Technische Bundesanstalt, Bundesallee 100, 38116 Braunschweig, Germany

¹²Los Alamos National Laboratory, Los Alamos, NM 87544, USA

ABSTRACT: Wendelstein 7-X (W7-X) is a large optimized stellarator ($B=2.5\text{T}$, $V=30\text{m}^3$) aiming at demonstrating the reactor relevance of the optimized stellarators. In summer this year (2015) W7-X will begin its first operation phase (OP1.1) with five inertially cooled inboard limiters made of graphite. Assuming the heat loads can be spread out evenly between the limiters, 1 second discharges at 2 MW of heating power could be run in OP1.1. The diagnostics available for this first operation phase, including some special limiter diagnostics, and their capabilities are being presented.

This paper will be published in the special 1st ECPD issue of JINST.

First EPS Conference on Plasma Diagnostics - 1st ECPD

14-17 April 2015,

Villa Mondragone , Frascati (Rome) Italy

^{*}Speaker